

Uncompromisingly cost-effective

SPECIAL MODEL



**Demag DC-Com
special chain hoist**

**100% longer service life –
50% higher duty factor**

DEMAG



Our **DC-Com special chain hoist** provides you with a Demag brand quality product with comprehensive features. Rated for a long service life and ideally suited for everyday needs. Based on our tried-and-tested DC-Com range, this special model boasts a high FEM classification and high duty factor.

All aluminium housing components have high-quality powder coating.

Available as a solo hoist or as a push-travel or electric-travel hoist unit.

Take advantage of our special model and its attractive price.

- 24 V contactor control
- High level of safety thanks to brake arranged in front of the slipping clutch in the load-bearing arrangement
- Reliable operation from -20 °C to +45 °C without any reduction in the duty factor, operation up to 60 °C also possible.
- Operating limit switches (upper and lower hook positions)
- Elapsed operating time counter
- Always convenient with main and creep lifting speeds
- Five types for load capacities up to 2,000 kg
- 4 m or 5 m hook path as standard
- Interface for electric travel
- Gearbox maintenance-free for up to 10 years

Load capacity [kg]	Chain hoist Type	Reeving	Group of mechanisms FEM/ISO	Lifting speeds [m/min]	
				at 50 Hz	at 60 Hz
125	DC-Com 1	1/1	3m/M6	8.0/2.0	9.6/2.4
250	DC-Com 2		2m/M5	6.0/1.5	7.2/1.8
500	DC-Com 5		2m/M5	4.5/1.1	5.4/1.3
1,000	DC-Com 10		2m/M5	4.0/1.0	4.8/1.2
2,000	DC-Com 10	2/1	2m/M5	4.0/1.0	4.8/1.2

For all sizes: 60% duty factor.

0820 EN/DE 213 733 44 700 IS 817
No liability for errors or omissions. Subject to change. Printed in Germany D/31082020/PDF

Demag
Cranes & Components GmbH
 Wetter Site
 Ruhrstrasse 28
 58300 Wetter, Germany
E info@demagcranes.com
T +49 2335 92 0
F +49 2335 92 7676
www.demagcranes.com

DEMAG